



Thrust Spherical Plain Bearings



型号	尺寸 (毫米)										/ kn			重量 □kg□	
	D	d□	B	c	H	dk	S	d	d	A	rs,r1s min	α ≈	静态静 态		动态
GX10S	10	30	7.50	7	9.50	32	7	27.50	15.50	3	0.60	5	27	136	0.04
GX12S	12	35	9.50	9.30	13	38	8	32	18	4	0.60	5	37	188	0.07
GX15S	15	42	11	10.80	15	46	10	39	22.50	5	0.60	6	53	267	0.11
GX17S	17	47	11.80	11.20	16	52	11	43.50	27	5	0.60	4	61	311	0.14
GX20S	20	55	14.50	13.80	20	60	12.50	50	31	6	1	5	84	425	0.25
GX25S	25	62	16.50	16.70	22.50	68	14	58.50	34.50	6	1	5	134	672	0.42
GX30S	30	75	19	19	26	82	17.50	70	42	8	1	5	182	909	0.61
GX35S	35	90	22	20.70	28	98	22	84	50.50	8	1	5	266	1330	0.97
GX40S	40	105	27	21.50	32	114	24.50	97	59	9	1	6	357	1810	1.59
GX45S	45	120	31	25.50	36.50	128	27.50	110	67	11	1	6	486	2470	2.24
GX50S	50	130	33	30.50	42.50	139	30	120	70	10	1	6	554	2810	3.14
GX60S	60	150	37	34	45	160	35	140	84	12.50	1	6	748	3820	4.63
GX70S	70	160	42	36.50	50	176	35	153	94.50	13.50	1	3	902	4610	5.37
GX80S	80	180	43.50	38	50	197	42.50	172	107.50	14.50	1	4	1110	5700	6.91
GX100S	100	210	51	46	59	222	45	198	127	15	1.10	4	1300	6470	11
GX120S	120	230	53.50	50	64	250	52.50	220	145	16.50	1.10	3	1530	7580	14
GX140S	140	260	61	54	72	274	52.50	243	177	23	1.50	3	1820	9040	19.10
GX160S	160	290	66	58	77	313	65	271	200	23	1.50	2	2100	10440	25
GX180S	180	320	74	62	86	340	67.50	299	225	26	1.50	4	2430	12070	32.80
GX200S	200	340	80	66	87	365	70	320	247	27	1.50	1	3070	15280	35.40